

# TRIO PVC – L

PVC emiř ve tařıma hortumu, hafif  
PVC suction and transport hose, lightweight



## Isı dayanımı

- ◆ -20°C +70°C
- ◆ Kısa süreli +80°C

## Temperature Range

- ◆ -20°C up to +70°C
- ◆ intermittent to +80°C

**DN 38 – DN 500**

## Malzeme

hortum duvarı: yumuřak PVC  
Spiral: yay elik tel

## Uygulamalar

- katılar iin emme ve tařıma hortumu
- kk toz paracıkları ve tozları tařıma
- oilspray tahliyesi
- klima / havalandırma
- koruma hortumu
- sıvı drenajı

## Özellikleri

- yađ, alkali ve asite karřı iyi diren
- iyi kimyasal diren
- neredeyse przsz i yzey
- En iyi akıř zellikleri
- son derece esnek
- hafif
- dřk dnme yarıapı

## Material

hose wall:soft PVC  
spiral:spring steel wire

## Applications

- suction and transport hose for solids, gaseous and liquid media
- transport of small dust particles and powders
- oilspray extraction
- air condition/ventilation
- protection hose
- liquid drainage

## Properties

- good resistance to oil,alkalis and acids
- good chemical resistance
- nearly smooth inside
- optimum flow characteristics
- extremely flexible
- lightweight
- small bend radius
- gas tight

## Konstrksiyon

Hortum duvarı: PVC  
Tel: yay elik tel  
Et kalınlıđı:0,7 mm

## Construction

immovable cast  
spring steel spiral  
hose wall:soft pvc  
wall thickness between spirals  
ca.0,7 mm



# TRIO PVC – L

ÇAP	Çalışma Basıncı	Vakum Basıncı	Dönme Yarıçapı	Dış çap	Ağırlık
DN	work.pressure ca.bar	low pressure ca.mm WG	bending radiusouter ca.mm	outer - Ø ca.mm	weight ca.kg/m
38	0,840	6750	46	46	0,41
40	0,840	6750	48	48	0,42
45	0,740	6000	53	53	0,44
50	0,670	5250	58	58	0,48
55	0,620	4500	63	63	0,54
60	0,560	4500	68	68	0,56
65	0,500	3750	73	73	0,68
70	0,450	3750	78	78	0,72
75	0,450	3000	84	84	0,76
80	0,390	3000	88	88	0,80
90	0,340	2250	99	99	0,93
100	0,340	2250	110	110	1,00
110	0,280	2250	119	119	1,09
115	0,280	2250	124	124	1,12
120	0,280	2250	129	129	1,18
125	0,280	2250	135	135	1,25
130	0,220	2250	139	139	1,27
140	0,220	1500	149	149	1,46
150	0,220	1500	161	161	1,56
160	0,220	1500	170	170	1,84
170	0,170	1500	180	180	1,90
175	0,170	1500	185	185	1,95
180	0,170	1500	190	190	2,01
200	0,170	1500	214	214	2,43
225	0,110	750	235	235	2,69
250	0,110	750	260	260	3,19
275	0,110	750	284	284	3,28
300	0,100	675	310	310	3,38
315	0,100	675	325	325	3,50
325	0,100	675	335	335	3,59
350	0,050	675	360	360	3,80
400	0,050	525	410	411	4,70
450	0,050	525	460	461	5,34
500	0,050	525	510	511	6,02



HAVA SİSTEMLERİ SAN. ve TİC. LTD. ŞTİ.

SALES ☎ : 0.322. 352 28 85 - 352 92 05 Fax: 359 46 92  
FACTORY ☎ : 0.322. 352 92 06 - 359 82 70  
Kızılay Cad. Ulucami Karşısı No:89 01010 Adana-TÜRKİYE  
www.unveren.com.tr • info@unveren.com.tr

